

**Features:**

- With ART System (Automatic Reset Test). In case of dry running, the system will automatically stop and periodically re-start
- Automatic recovery of system settings after a power failure
- Built-in pressure transmitter with digital display
- Recording of operations and thus information about operating hours, number of starts, number of power interruptions. Alarm recording: Type and number of alarm messages from the date of commissioning
- STC function (Smart Temperature Control): If the electronics assembly / the converter reaches a temperature of 85°C, the frequency will be slowed. This way, the temperature is decreased, but the water flow is kept.
- Designed for wall mounting
- Supply voltage 1x230 V (1010 MT) or 3x400 V (1309 TT)


**Application:**

- Pump control by means of frequency converter. It can control an individual pump or 2 pumps in combination (master-slave mode with alternating pump activation)

**Scope of delivery:**

- Pressure sensor included in scope of delivery

**Product benefits:**

- Aluminium heat exchanger
- Control and information panel with LCD screen
- insulation-protected PVC housing IP55
- PG connection with strain relief
- Alarm recording
- Auto-reset function
- large setting range of operating pressure 0.5 – 16 bar

**Technical data:**

| Art.no. | U<br>[V] | Weight<br>[kg] |
|---------|----------|----------------|
| 20295   | 230      | 4,5            |