

sludge suction cleaner quad-pump

Features:

- Professional suction cleaner as mobile, controllable, quadruple diaphragm pump
- suction head up to 6,5 m
- unlike conventional centrifugal pumps dry-run does not damage the pump, the diaphragm technique even allows dry suction filling of pump housing or hoses is not required
- The USS 7000 must not be used for oily media. The USS 8000 is suitable for oily media.

Application:

• universal drainage or cleaning (flooded and silty cellars, swimming pools etc.)

Scope of delivery:

- pre-assembled ready for connection with 10 m power cable and plug
- 3,5 m 1" suction hose and discharge hose
- 3 suction nozzles
- 3 stainless steel suction pipes 0,5 m




Product benefits:

- powerful and variable quadruple diaphragm pump technology
- suitable for dry-run
- extensive standard accessories
- oil-proof (version USS 8000)

Technical data:

| Art.no. | U [V] | P ₁ [W] | P ₂ [W] | ln [A] | Qmax [m³/h] | Hmax [m] | SH [mm] | PO | L [mm] | W [mm] | H [mm] | Weight [kg] |
|---------|----------|-----------------------|-----------------------|-----------|----------------|-------------|------------|--------|-----------|-----------|-----------|----------------|
| 15653 | 230 | 1.000 | 750 | 3,7 | 5,8 | 12,0 | 15 | G 11/4 | 893 | 503 | 733 | 67 |

Characteristics:





Dimensions:

