

Features:

- polyethylene container with 35 litres capacity and up to 20 litres switching volume
- built-in waste water pump ZPK with float switch
- connection for air vent and cable gland DN 50 (HT)
- inlet connection piece DN 50 is included - installable by drilling a hole in the container
- pressure outlet 1 1/4" with integrated non-return valve
- operation temperature 40°C (short-term 90°C)
- protection grade IP 68 - fully submersible

Application:

- pumping of domestic waste water from washing machines, showers, washbasins etc.
- below-ground installation in frost-free rooms below the backflow level

Scope of delivery:

- pre-assembled ready for connection with 10 m power cable and plug
- accessible plastic grade, siphon, sand-trap
- inlet connection piece DN 50
- extended top section and closed cover plate available as accessories




Product benefits:

- ready for connection - pump and control unit already integrated
- integrated siphon for prevention of odour nuisance
- pre-drilled additional inlets possible

Technical data:

Art.no.	U [V]	P ₁ [W]	P ₂ [W]	In [A]	n [min ⁻¹]	Q _{max} [m ³ /h]	H _{max} [m]	SH [mm]	P0	Weight [kg]
11491	230	300	130	1,3	2800	7,0	7,5	10	G 1 1/4	6,1

Characteristics:



Materials:

Material impeller:	PA6 GV25
Seal motor:	shaft seal NBR
Seal pump:	mechanical seal carbon/ceramic/NBR
Material motor housing:	stainless steel AISI 316L
Material pump housing:	PP GF20
Material motor shaft:	stainless steel AISI 430F
Material container:	PE

Dimensions:

